In The Claims

1. (Currently Amended) A compound for enhancing the physical properties of a material having pliantcy, durability, and imperviousness, said compound comprising:

from about 55 to about 75 65.5% by weight a first polymer resin; from about 20 to about 30 28% by weight a second polymer; and from about 1 to about 15 5% by weight an emulsifier; and from about 1.5% by weight a defoamer; wherein said compound is mixed with an asphalt emulsion; and

wherein said <u>first polymer resin</u> and said <u>second</u> polymer change at least one of said pliantcy, durability, and imperviousness of the material; and [[.]]

wherein said first polymer is a vinyl acrylic polymer and said second polymer is a styrene-butadiene copolymer and said emulsifier is anionic.

- 2. 4. (Withdrawn)
- 5. (Original) The compound of claim 1, wherein said asphalt emulsion is cationic.

- 6. (Original) The compound of claim 1, wherein said asphalt emulsion is anionic.
- 7. (Original) The compound of claim 1, wherein said asphalt emulsion comprises about 25 % by weight of the conditioner.
- 8. 15. (Withdrawn)
- 16. (Currently Amended) A method of enhancing and conditioning the physical properties of a material comprising:

applying to said material a compound comprising from about 65.5% by weight a first polymer, from about 28% by weight, a second polymer, from about 5% by weight an emulsifier, and from about 1.5% by weight defoamer;

wherein said first polymer and said second polymer change at least one of said pliantcy, durability, and imperviousness of the material;

wherein said first polymer is a vinyl acrylic polymer and said second polymer is a styrene-butadiene copolymer and said emulsifier is anionic; and

wherein said compound is applied to soil at a rate of about 0.21 to about 0.42 gallons per cubic yard. a resin, a polymer, and an emulsifier.

17. – 24. (Withdrawn)

25. (Original) The method of claim 16 wherein the applying of said compound is applied by mechanical mixing.

26. - 31. (Withdrawn)

32. (Original) The method of claim 16 wherein said compound is applied to said material at a depth of about 3 inches.

33. - 37. (Withdrawn)

Please enter the following amendments and remarks:

Please enter the following amendments and remarks:

STATUS OF THE CLAIMS

Claims 1-37 are pending in the Application.

Claims 1-37 have been rejected by the Examiner.

Claims 2-4, 8-15, 17-24, 36-31 and 33-37 have been withdrawn from consideration, subject to reservation of the right to prosecute those claims, or the subject matter thereof, in this or a subsequent application.

Reconsideration of the present Application is respectfully requested.